

▶ 650c & 525c Coaxial Ceiling Speakers

Specifications:



SYSTEM	650c	525c
Frequency Range (-10 dB):	45 Hz to 22kHz	55 Hz to 22 kHz
Power Rating:	70 watts	60 watts
Sensitivity:	90 dB	88 dB
Nominal Impedance:	4 ohms	4 ohms
Crossover Frequency:	5 kHz	5 kHz
LOW-FREQUENCY TRANSDUCER		
Nominal Diameter & Material:	165 mm (6.5 in.) polypropylene cone	133 mm (5.25 in.) polypropylene cone
Voice Coil:	25.01 mm (1.0 in.)	25 mm (1.0 in.)
Magnetic Assembly Weight:	10 oz.	10 oz.
HIGH-FREQUENCY TRANSDUCER		
Nominal Diameter & Material:	13 mm (0.5 in.) polymer-titanium composite	13 mm (0.5 in.) polymer-titanium composite
Voice Coil:	13 mm (0.5 in.)	13 mm (0.5 in.)
Magnetic Assembly Weight:	1 oz.	1 oz.
GENERAL		
Outside Dimensions:	230 mm (9.06 in.) diameter	205 mm (8.07 in.) diameter
Input Connectors:	Spring-loaded push-in terminals	Spring-loaded push-in terminals
Mounting Hardware:	Included	Included

JBL continually engages in research related to product improvement. New materials, production methods and design refinements are introduced into existing products without notice as a routine expression of that philosophy. For this reason, any current JBL product may differ in some respect from its published description but will always equal or exceed the original design specifications unless otherwise noted.

Harman Residential Group
8500 Balboa Boulevard, P.O. Box 2200
Northridge, California 91329 USA

MA Harman International Company

5K 2/97