



JBL STUDIO™ 190

Dual 6.5-inch (165mm) Floorstanding Loudspeaker

Powerful, accurate and styled to make a dramatic design statement in any listening environment, JBL Studio™ 190 floorstanding loudspeakers employ performance-proven technologies and advanced materials to deliver the dynamic range, tonal accuracy and spatial transparency that have long been hallmarks of the legendary JBL sound. Featuring dual woofers and midrange drivers with high-output PolyPlas™ cones, and CMMD® Lite tweeter domes with proprietary Bi-Radial® waveguides, Studio 190 systems offer exceptional clarity and realism with outstanding bass response. Use them in combination with other Studio 1 Series speakers for a truly cinematic home theater experience, or use them alone to hear your favorite music like you've never heard it before.

TECHNICAL SPECIFICATIONS

Speaker type:	3-1/2-way dual floorstanding
Low-frequency transducers:	Two 6-1/2" (165mm) PolyPlas cones, magnetically shielded
Midrange transducer:	4" (100mm) PolyPlas cone, magnetically shielded
High-frequency transducer:	1" CMMD Lite dome, magnetically shielded, in a Bi-Radial constant directivity waveguide
Recommended amplifier power:	200 watts
Frequency response:	45Hz – 22kHz (–3dB)
Nominal impedance:	8 ohms
Sensitivity (2.83V/1m):	88dB
Crossover frequencies:	800Hz, 3.2kHz, 6dB/octave
Enclosure type:	Ported, with midrange subenclosure
Connector type:	Dual gold-plated binding posts (bi-wire capable)
Available finishes:	Black (BK)
Dimensions (H x W x D):	44-1/8" x 7-7/8" x 14-3/4" (1121mm x 200mm x 375mm)
Weight:	48.8 lb (22.1kg)

JBL STUDIO™ 190

Dual 6.5-inch (165mm) Floorstanding Loudspeaker



HIGHLIGHTS

Dual 6.5" (165mm) Low-Frequency Transducers

- Stiff, lightweight ribbed PolyPlas cones with rubber surrounds
- Powerful bass response with low distortion
- Magnetically shielded for placement near TV

4" (100mm) Midrange Transducer

- Stiff, lightweight PolyPlas cone with cloth surround
- Separate sub-enclosure isolates midrange frequencies for improved clarity
- Magnetically shielded for placement near TV

1" (25mm) High-Frequency Transducer

- CMMD Lite dome with JBL Bi-Radial waveguide
- Eliminates unwanted resonances for clear, extended high-frequency response
- Distributes HF more directly, over a wider listening area
- Magnetically shielded for placement near TV

Dynamic JBL Weave Design

- Distinctive, one-of-a-kind look

KEY FEATURES

- Tower configuration places midrange and HF transducers at ear level
- Rigid, heavily braced 3/4" (19mm) MDF enclosure
- Rear-facing bass port increases output and extends bass response
- Dual gold-plated binding posts with bi-wire capability increases connection options
- Available in silver-tinted black vinyl finish



Harman Consumer, Inc
8500 Balboa Blvd., Northridge, CA 91329 USA
www.jbl.com



© 2010 Harman International Industries, Incorporated. All rights reserved. JBL, Bi-Radial and CMMD are registered trademarks of Harman International Industries, Incorporated. Studio Series and PolyPlas are trademarks of Harman International Industries, Incorporated.

Features, specifications and appearance are subject to change without notice.